
# EXHIBIT D

U.S. Patent No. US 9,448,603 v. Samsung

### 1. Claim Chart

Claim	Analysis
[1.P] A method for transferring	Samsung ("Company") performs and/or induces others to perform a method for transferring power to a receptor mobile device from a donor mobile device having a battery.
power to a receptor	This element is infringed literally, or in the alternative, under the doctrine of equivalents.
mobile device from a donor mobile device having	For example, Company provides mobile devices such as Galaxy and Foldable smartphones and smartwatches including, but not limited to, the Galaxy S20 series, Galaxy smartwatches and Galaxy Z fold phones, that comprise a feature of 'Wireless PowerShare' or 'Reverse Charging' and are compliant with Qi, a standard for wireless power transfer.
a battery,	Further, in PowerShare, the power is transferred wirelessly from the battery of one Galaxy device such as a smartphone
comprising;	("donor mobile device") to the battery of another Galaxy device such as a smartwatch ("receptor mobile device") such that the smartwatch gets charged.  Wireless PowerShare  Put the center of your phone back to back with another device.  Source: <a href="https://www.youtube.com/watch?v=MrJzQVnrGdU&amp;t=12s">https://www.youtube.com/watch?v=MrJzQVnrGdU&amp;t=12s</a> at 0:12



Most Qi-Compatible Samsung devices can be charged with Wireless PowerShare, but check out the full list of compatible devices below just in case. The speed and power of the charge will vary by device.

- Galaxy Note phones: Galaxy Note20 5G, Note20 Ultra 5G, Note10+, Note10, Note9, Note8, and Note 5
- Galaxy S phones: S23 series, S22 series, S21 series, S20 series, S10 series, S9 series, S8 series, S7 series, and S6 series
- Foldable phones: Galaxy Z Fold, Z Fold2, Z Fold3, Z Fold4, Z Fold5, Z Flip, Z Flip 5G, Z Flip3, Z Flip4, and Z Flip5
- Samsung earbuds: Galaxy Buds Pro, Galaxy Buds Pro 2, Galaxy Buds Live, Galaxy Buds+, Galaxy Buds2, and Galaxy Buds
- Samsung smart watches: Galaxy Watch 5 Pro, Galaxy Watch5, Galaxy Watch4, Galaxy Watch4 Classic, Galaxy Watch, Galaxy Watch3, Galaxy Watch Active, and Galaxy Watch Active2
- Additional devices: Galaxy S7/S7 Edge, Galaxy S8/S8+, and Galaxy S9/S9+

Source: https://www.samsung.com/us/support/answer/ANS00047798/

Charging your devices can easily become a tangled mess. Fortunately, Samsung is here to help with our wireless charging options. Between our PowerShare technology and our wireless charging pads, like the **Wireless Charger Duo**, you no longer have to worry about accidentally yanking the charger out of the wall when you pick up your attached phone. Depending on which **wireless charger** you have, you can charge up to three devices at once. With PowerShare, you can charge a compatible phone, smart watch, or earbuds by placing it on your Galaxy phone.

Source: https://www.samsung.com/us/support/answer/ANS00047798/

Further, to the extent this element is performed at least in part by Defendant's software source code, Plaintiff shall supplement these contentions pursuant to production of such source code by the Company.

[1.1]Company performs and/or induces others to perform a method of configuring a donor wireless power transfer mechanism configuring a on the donor mobile device using a wireless transmit application. donor wireless This element is infringed literally, or in the alternative, under the doctrine of equivalents. power transfer For example, when the Galaxy smartphone has sufficient battery, the Wireless PowerShare setting ("wireless transmit mechanism application") is turned on in the smartphone to charge the smartwatch. on the donor mobile device using Galaxy S20 5G Galaxy S20 FE 5G wireless transmit application; **Charging**<sup>5</sup> Super Fast Charging Super Fast Charging Fast Wireless Charging 2.0 Fast Wireless Charging 2.0 Wireless PowerShare Wireless PowerShare Source: https://www.samsung.com/global/galaxy/compare-smartphones/



### Remove third-party cases or covers from both devices.

Wireless power sharing will not work through particularly thick cases, and some materials may prevent charging. Remove any third-party cases or covers from your Galaxy phone and Samsung device with Qi charging standard.

You should also remove headphones. Do not use any while sharing power because doing so may affect nearby devices.



### Make sure the phone that is providing power has sufficient charge.

If the phone sharing power has less than 30 percent battery and is not plugged in, Wireless power sharing will not turn on.

However, if you charge the phone while wirelessly charging another device, the charging speed may decrease or the device may not charge properly.




### Turn on Wireless power sharing.

On the phone with **Wireless power sharing**, swipe down from the top of the screen with two fingers to access the Quick Settings panel. Then, Swipe to and tap the **Wireless** power sharing icon to turn on the feature.

**Note**: You can also charge both devices with one cable. After turning on Wireless power sharing, connect the two devices using your included charger, both devices will charge simultaneously.

Source: https://www.samsung.com/us/support/troubleshooting/TSG01109653/



Source: https://www.samsung.com/us/support/answer/ANS00047798/


Further, to the extent this element is performed at least in part by Defendant's software source code, Plaintiff shall supplement these contentions pursuant to production of such source code by the Company.

[1.2] configuring a receptor wireless power transfer mechanism on the receptor mobile device using a wireless

Company performs and/or induces others to perform a method of configuring a receptor wireless power transfer mechanism on the receptor mobile device using a wireless receive application.

This element is infringed literally, or in the alternative, under the doctrine of equivalents.

For example, the Galaxy smartwatch is placed back-to-back on the Galaxy smartphone such that the smartwatch gets charged. Therefore, it would be apparent that the smartwatch comprises a wireless receive application that is activated such that the smartwatch starts getting charged.



Source: <a href="https://www.samsung.com/global/galaxy/compare-smartphones/">https://www.samsung.com/global/galaxy/compare-smartphones/</a>

Further, to the extent this element is performed at least in part by Defendant's software source code, Plaintiff shall supplement these contentions pursuant to production of such source code by the Company.

[1.3] transferring power from donor mobile device to the receptor mobile device using the donor wireless power transfer mechanism and the receptor wireless power transfer mechanism: and

Company performs and/or induces others to perform a method of transferring power from donor mobile device to the receptor mobile device using the donor wireless power transfer mechanism and the receptor wireless power transfer mechanism.

This element is infringed literally, or in the alternative, under the doctrine of equivalents.

For example, when the Wireless PowerShare feature is enabled in Qi-compatible devices, the power is transferred from the smartphone to the smartwatch through a Qi wireless power transfer system using magnetic induction ("the donor wireless power transfer mechanism and the receptor wireless power transfer mechanism").

Most Qi-Compatible Samsung devices can be charged with Wireless PowerShare, but check out the full list of compatible devices below just in case. The speed and power of the charge will vary by device.

- Galaxy Note phones: Galaxy Note20 5G, Note20 Ultra 5G, Note10+, Note10, Note9, Note8, and Note 5
- Galaxy S phones: S23 series, S22 series, S21 series, S20 series, S10 series, S9 series, S8 series, S7 series, and S6 series
- Foldable phones: Galaxy Z Fold, Z Fold2, Z Fold3, Z Fold4, Z Fold5, Z Flip, Z Flip 5G, Z Flip3, Z Flip4, and Z Flip5
- Samsung earbuds: Galaxy Buds Pro, Galaxy Buds Pro 2, Galaxy Buds Live, Galaxy Buds+, Galaxy Buds2, and Galaxy Buds
- Samsung smart watches: Galaxy Watch 5 Pro, Galaxy Watch5, Galaxy Watch4, Galaxy Watch4 Classic, Galaxy Watch, Galaxy Watch3, Galaxy Watch Active, and Galaxy Watch Active2
- Additional devices: Galaxy S7/S7 Edge, Galaxy S8/S8+, and Galaxy S9/S9+

Source: https://www.samsung.com/us/support/answer/ANS00047798/

The Qi wireless power transfer system uses magnetic induction to transfer power from a Power Transmitter Product (charger) to a Power Receiver Product (smartphone).

Source: <a href="https://www.wirelesspowerconsortium.com/knowledge-base/specifications/download-the-qi-specifications/V-1.3-introduction">https://www.wirelesspowerconsortium.com/knowledge-base/specifications/download-the-qi-specifications/V-1.3-introduction</a>

Further, to the extent this element is performed at least in part by Defendant's software source code, Plaintiff shall supplement these contentions pursuant to production of such source code by the Company.

[1.4] receiving and converting received power into electric current using the receptor wireless power transfer mechanism;

Company performs and/or induces others to perform a method of receiving and converting received power into electric current using the receptor wireless power transfer mechanism.

This element is infringed literally, or in the alternative, under the doctrine of equivalents.

For example, the Qi wireless power transfer system uses magnetic induction to transfer power from the power transmitter to the power receiver. Further, when charging begins, the magnetic field is picked up by the coil inside the Power Receiver and transformed by a power converter back into a direct electrical current that can be used to charge the battery.

# 3 How Qi wireless power transfer works

## 3.1 Basic concepts

The Qi wireless power transfer system uses magnetic induction to transfer power from a Power Transmitter Product (charger) to a Power Receiver Product (smartphone).

Source: <a href="https://www.wirelesspowerconsortium.com/knowledge-base/specifications/download-the-qi-specifications/V-1.3-introduction">https://www.wirelesspowerconsortium.com/knowledge-base/specifications/download-the-qi-specifications/V-1.3-introduction</a>, Page 8

When charging begins, the Power Transmitter runs an alternating electrical current through its coil(s), which generates an alternating magnetic field in accordance with Faraday's law. This magnetic field is in turn picked up by the coil inside the Power Receiver and transformed by a power converter back into a direct electrical current that can be used to charge the battery.

A critical feature of the magnetic field is that it can transfer through any non-metallic, non-ferrous materials, such as plastics, glass, water, wood, and air. In other words, wires and connectors are not needed between the Power Transmitter Product and Power Receiver Product.

PRx coil in smartphone

Magnetic field

PTx coil in charging pad

Figure 6. Qi wireless power transfer using magnetic induction

Source: <a href="https://www.wirelesspowerconsortium.com/knowledge-base/specifications/download-the-qi-specifications/V-1.3-introduction">https://www.wirelesspowerconsortium.com/knowledge-base/specifications/download-the-qi-specifications/V-1.3-introduction</a>, Page 9

Further, to the extent this element is performed at least in part by Defendant's software source code, Plaintiff shall supplement these contentions pursuant to production of such source code by the Company.


[1.5] wherein the donor wireless power transfer mechanism includes primary coil donor and circuit elements and the receptor wireless power transfer mechanism includes secondary coil, receptor circuit elements and capacitor such that the donor circuit elements provide electric current to the primary coil producing a magnetic field that

Company performs and/or induces others to perform a method of transferring power, wherein the donor wireless power transfer mechanism includes a primary coil and donor circuit elements and the receptor wireless power transfer mechanism includes a secondary coil, receptor circuit elements and a capacitor such that the donor circuit elements provide electric current to the primary coil producing a magnetic field that generates an electric current in the secondary coil and the receptor circuit elements thereby transferring power from donor mobile device to the receptor mobile device, the capacitor storing electric charge that increases battery life when the capacitor is discharged.

This element is infringed literally, or in the alternative, under the doctrine of equivalents.

For example, when charging begins, the power transmitter, that comprises an inverter, series capacitor ("donor circuit elements") and a coil ("primary coil"), runs an alternating electrical current through its coil, which generates an alternating magnetic field following Faraday's law. This magnetic field is in turn picked up by the coil ("secondary coil") inside the power receiver and transformed by a power converter back into a direct electrical current that can be used to charge the battery.

Further, the power receiver circuitry comprises a series capacitor, and a rectifier ("receptor circuit elements") such that the battery in the receiver gets charged. Further, the power receiver sends a signal to stop the power transfer to the power transmitter when wireless power is not required. Therefore, it would be apparent to a person having ordinary skill in the art that the capacitor is used for storing an electric charge which further increases the battery life of the power receiver.



**Power Signal:** An alternating magnetic field.

**Supply Power:** The power dissipated from the supply.

**Power Transmitter:** A subsystem that can generate a Power Signal.

**Power Transmitter Product:** 

A device containing one or more Power Transmitters.

**Transmitted Power:** The power from the Power Signal dissipated by any object that is not an

integral part of the Power Transmitter Product.

**Power Receiver:** A subsystem that can extract electric power from a Power Signal.

**Power Receiver Product:** 

A device containing a Power Receiver.

**Received Power:** The power from the Power Signal dissipated by any component that is

an integral part of the Power Receiver Product.

Source: <a href="https://www.wirelesspowerconsortium.com/knowledge-base/specifications/download-the-qi-specifications/V-1.3-Power Delivery">https://www.wirelesspowerconsortium.com/knowledge-base/specifications/download-the-qi-specifications/V-1.3-Power Delivery</a>

When charging begins, the Power Transmitter runs an alternating electrical current through its coil(s), which generates an alternating magnetic field in accordance with Faraday's law. This magnetic field is in turn picked up by the coil inside the Power Receiver and transformed by a power converter back into a direct electrical current that can be used to charge the battery.

A critical feature of the magnetic field is that it can transfer through any non-metallic, non-ferrous materials, such as plastics, glass, water, wood, and air. In other words, wires and connectors are not needed between the Power Transmitter Product and Power Receiver Product.

PRx coil in smartphone

Magnetic field

PTx coil in charging pad

Primary Coil

Figure 6. Qi wireless power transfer using magnetic induction

Source: <a href="https://www.wirelesspowerconsortium.com/knowledge-base/specifications/download-the-qi-specifications/V-1.3-introduction">https://www.wirelesspowerconsortium.com/knowledge-base/specifications/download-the-qi-specifications/V-1.3-introduction</a>, Page 9

Figure 11 illustrates a simplified model of the system comprising a Power Transmitter on the left and a Power Receiver on the right. For clarity, the load circuit is drawn separately from the Power Receiver. The Power Transmitter consists of a power source  $(u_{\rm op}, f_{\rm op})$ , a capacitance  $C_{\rm p}$ , an inductance  $L_{\rm p}$ , and a resistance  $R_{\rm p}$ . The power source supplies a sinusoidal voltage  $u_{\rm op}$  at a frequency  $f_{\rm op}$ . The Power Receiver consists of a capacitance  $C_{\rm s}$ , an inductance  $L_{\rm s}$ , and a resistance  $R_{\rm s}$ .

A load having an impedance  $Z_L$  is connected to the output terminals of the Power Receiver. The symbols  $u_L$ ,  $i_L$ ,  $i_p$ , and  $k_{op}$  represent the load voltage, load current, Primary Coil current, and coupling factor.

Capacitor

Capacitor

PTx

Power


Transfer

Interface

Figure 11. Simplified system model


Source: <a href="https://www.wirelesspowerconsortium.com/knowledge-base/specifications/download-the-qi-specifications/V-1.3-Power\_Delivery">https://www.wirelesspowerconsortium.com/knowledge-base/specifications/download-the-qi-specifications/V-1.3-Power\_Delivery</a>, Page 33

	It is recommended that the Power Transmitter Product's power consumption in stand-by mode of
	operation meets the Energy Star EPS Requirements for "Energy consumption for No-Load" and the
	European Commission, Code of Conduct of Energy Efficiency of External Power Supplies for "No-
	load power consumption." It is also recommended that a Power Receiver is designed in a manner
	that when wireless power is not required, the Power Receiver will send an End Power Transfer
	Packet to put the Power Transmitter Product in stand-by mode.
	Source: <a href="https://www.wirelesspowerconsortium.com/knowledge-base/specifications/download-the-qi-specifications/V-1.3-Power_Delivery">https://www.wirelesspowerconsortium.com/knowledge-base/specifications/download-the-qi-specifications/V-1.3-Power_Delivery</a> , Page 45
	Further, to the extent this element is performed at least in part by Defendant's software source code, Plaintiff shall supplement these contentions pursuant to production of such source code by the Company.
[2] The method of claim 1,	Company performs and induces others to perform the method of claim 1, further comprising configuring a donor power threshold using a wireless transmit application.
further comprising	This element is infringed literally, or in the alternative, under the doctrine of equivalents.
configuring a donor power threshold	For example, the Wireless PowerShare feature is enabled when the battery of the smartphone is at a certain level such as 30%, and stops transferring the power if the battery level goes beyond this percentage. Therefore, it would be apparent to a person having ordinary skill in the art that a donor power threshold is configured while setting the PowerShare
using a wireless	feature.
transmit application.	



Source: https://www.youtube.com/watch?v=YcGLPV8Ov-o at 1:00

	Further, to the extent this element is performed at least in part by Defendant's software source code, Plaintiff shall supplement these contentions pursuant to production of such source code by the Company.
[3] The	
method of	Company performs and induces others to perform the method of claim 2, further comprising determining whether the
claim 2,	donor mobile device has been reduced to the donor power threshold.
further	This element is infringed literally, or in the alternative, under the doctrine of equivalents.
comprising	This element is intringed inerally, of in the alternative, under the docume of equivalents.
determining	For example, the wireless power sharing between the two devices will stop if the battery percentage of the power
whether the	transmitter reaches a battery limit ("donor power threshold") set by a user.
donor mobile	dunishmeer reaches a sactory mine ( donor power amesmola ) set by a user.
device has	
been reduced	
to the donor	
power	
threshold.	



Source: <a href="https://www.youtube.com/watch?v=YcGLPV8Ov-o">https://www.youtube.com/watch?v=YcGLPV8Ov-o</a> at 1:00

Further, to the extent this element is performed at least in part by Defendant's software source code, Plaintiff shall supplement these contentions pursuant to production of such source code by the Company.

[4] The method of claim 1, further comprising configuring a receptor power threshold using a wireless receive application.

Company performs and induces others to perform the method of claim 1, further configuring a receptor power threshold using a wireless receive application.

This element is infringed literally, or in the alternative, under the doctrine of equivalents.

For example, in the Qi wireless power transfer system, the power receiver or the smartwatch includes an output disconnect switch, which gets activated when the power receiver reaches a voltage peak. Furthermore, a Power Receiver is designed in a manner that when wireless power is not required, the Power Receiver will send an End Power Transfer Packet to put the Power Transmitter in standby mode. Therefore, it would be apparent to a person having ordinary skill in the art that the smartwatch gets charged until the battery of the smartwatch reaches a specific power threshold.

• An output disconnect switch, which prevents current from flowing to the output when the Power Receiver does not provide power at its output. In addition, the output disconnect switch prevents current back flow into the Power Receiver when the Power Receiver does not provide power at its output. Moreover, the output disconnect switch minimizes the power that the Power Receiver draws from the Power Transmitter when a Power Signal is first applied to the Secondary Coil.

Source: <a href="https://www.wirelesspowerconsortium.com/knowledge-base/specifications/download-the-qi-specifications/V-1.3-Power\_Delivery">https://www.wirelesspowerconsortium.com/knowledge-base/specifications/download-the-qi-specifications/V-1.3-Power\_Delivery</a>, Page 13

The Power Receiver shall have the means to disconnect its output from the subsystems connected thereto. If the Power Receiver has disconnected its output, it shall ensure that it still draws a sufficient amount of power from the Power Transmitter, such that Power Receiver to Power Transmitter communications remain possible (see *Qi Specification, Communications Physical Layer*).

The Power Receiver shall keep its output disconnected until it reaches the *power transfer* phase for the first time after a Digital Ping (see the *Qi Specification, Communications Protocol*). Subsequently, the Power Receiver may operate the output disconnect switch any time while the Power Transmitter applies a Power Signal.

**NOTE:** The Power Receiver may experience a voltage peak when operating the output disconnect switch (and changing between maximum and near-zero power dissipation).

Source: <a href="https://www.wirelesspowerconsortium.com/knowledge-base/specifications/download-the-qi-specifications/V-1.3-Power Delivery">https://www.wirelesspowerconsortium.com/knowledge-base/specifications/download-the-qi-specifications/V-1.3-Power Delivery</a>, Page 17

It is recommended that the Power Transmitter Product's power consumption in stand-by mode of operation meets the Energy Star EPS Requirements for "Energy consumption for No-Load" and the European Commission, Code of Conduct of Energy Efficiency of External Power Supplies for "No-load power consumption." It is also recommended that a Power Receiver is designed in a manner that when wireless power is not required, the Power Receiver will send an End Power Transfer Packet to put the Power Transmitter Product in stand-by mode.

Source: <a href="https://www.wirelesspowerconsortium.com/knowledge-base/specifications/download-the-qi-specifications/V-1.3-Power\_Delivery">https://www.wirelesspowerconsortium.com/knowledge-base/specifications/download-the-qi-specifications/V-1.3-Power\_Delivery</a>, Page 45

[8-P] A method for transferring power to a receptor mobile device from a donor mobile device having a battery, comprising;

Samsung ("Company") performs and induces others to perform a method for transferring power to a receptor mobile device from a donor mobile device having a battery.


This element is infringed literally, or in the alternative, under the doctrine of equivalents.

For example, Company provides mobile devices such as Galaxy and Foldable smartphones and smartwatches including, but not limited to, the Galaxy S20 series, Galaxy smartwatches and Galaxy Z fold phones, that comprise a feature of 'Wireless PowerShare' or 'Reverse Charging' and are compatible with Qi, a standard for wireless power transfer.

Further, in PowerShare, the power is transferred wirelessly from a battery of one Galaxy device such as a smartphone ("donor mobile device") to the battery of another Galaxy device such as a smartwatch ("receptor mobile device") such that the smartwatch gets charged.



Source: https://www.youtube.com/watch?v=MrJzQVnrGdU&t=12s at 0:12




Source: <a href="https://www.youtube.com/watch?v=MrJzQVnrGdU&t=12s">https://www.youtube.com/watch?v=MrJzQVnrGdU&t=12s</a> at 0:17

Most Qi-Compatible Samsung devices can be charged with Wireless PowerShare, but check out the full list of compatible devices below just in case. The speed and power of the charge will vary by device.

- Galaxy Note phones: Galaxy Note20 5G, Note20 Ultra 5G, Note10+, Note10, Note9, Note8, and Note 5
- Galaxy S phones: S23 series, S22 series, S21 series, S20 series, S10 series, S9 series, S8 series, S7 series, and S6 series
- Foldable phones: Galaxy Z Fold, Z Fold2, Z Fold3, Z Fold4, Z Fold5, Z Flip, Z Flip 5G, Z Flip3, Z Flip4, and Z Flip5
- Samsung earbuds: Galaxy Buds Pro, Galaxy Buds Pro 2, Galaxy Buds Live, Galaxy Buds+, Galaxy Buds2, and Galaxy Buds
- Samsung smart watches: Galaxy Watch 5 Pro, Galaxy Watch5, Galaxy Watch4, Galaxy Watch4 Classic, Galaxy Watch, Galaxy Watch3, Galaxy Watch Active, and Galaxy Watch Active2
- Additional devices: Galaxy S7/S7 Edge, Galaxy S8/S8+, and Galaxy S9/S9+

	Source: https://www.samsung.com/us/support/answer/ANS00047798/
	Charging your devices can easily become a tangled mess. Fortunately, Samsung is here to help with our wireless charging options. Between our PowerShare technology and our wireless charging pads, like the <b>Wireless Charger Duo</b> , you no longer have to worry about accidentally yanking the charger out of the wall when you pick up your attached phone. Depending on which <b>wireless charger</b> you have, you can charge up to three devices at once. With PowerShare, you can charge a compatible phone, smart watch, or earbuds by placing it on your Galaxy phone.
	Source: https://www.samsung.com/us/support/answer/ANS00047798/
	Further, to the extent this element is performed at least in part by Defendant's software source code, Plaintiff shall supplement these contentions pursuant to production of such source code by the Company.
[8.1] configuring a wireless	Company performs and induces others to perform the method of configuring a wireless power transfer mechanism on the receptor mobile device using a wireless receive application.
power transfer	This element is infringed literally, or in the alternative, under the doctrine of equivalents.
mechanism on the receptor mobile	For example, the Galaxy smartwatch is placed back-to-back on the Galaxy smartphone such that the smartwatch gets charged. Therefore, it would be apparent that the smartwatch comprises a wireless receive application that is activated such that the smartwatch starts getting charged.
device using	
a wireless receive	
application;	



	Source: https://www.samsung.com/global/galaxy/compare-smartphones/
	Further, to the extent this element is performed at least in part by Defendant's software source code, Plaintiff shall supplement these contentions pursuant to production of such source code by the Company.
[8.2] determining a receptor	Company performs and induces others to perform the method of determining a receptor power threshold using a wireless receive application.
power threshold	This element is infringed literally, or in the alternative, under the doctrine of equivalents.
using a wireless receive application;	For example, in the Qi wireless power transfer system, the power receiver or the smartwatch includes an output disconnect switch, which gets activated when the power receiver reaches a voltage peak. Furthermore, a Power Receiver is designed in a manner that when wireless power is not required, the Power Receiver will send an End Power Transfer Packet to put the Power Transmitter in standby mode. Therefore, it would be apparent to a person having ordinary skill in the art that the smartwatch gets charged until the battery of the smartwatch reaches a specific power threshold.  • An output disconnect switch, which prevents current from flowing to the output when the Power Receiver does not provide power at its output. In addition, the output disconnect switch prevents current back flow into the Power Receiver when the Power Receiver does not provide power at its output. Moreover, the output disconnect switch minimizes the power that the
	Power Receiver draws from the Power Transmitter when a Power Signal is first applied to the
	Secondary Coil.
	Source: <a href="https://www.wirelesspowerconsortium.com/knowledge-base/specifications/download-the-qi-specifications/V-1.3-Power_Delivery">https://www.wirelesspowerconsortium.com/knowledge-base/specifications/download-the-qi-specifications/V-1.3-Power_Delivery</a>

The Power Receiver shall have the means to disconnect its output from the subsystems connected thereto. If the Power Receiver has disconnected its output, it shall ensure that it still draws a sufficient amount of power from the Power Transmitter, such that Power Receiver to Power Transmitter communications remain possible (see *Qi Specification, Communications Physical Layer*).

The Power Receiver shall keep its output disconnected until it reaches the *power transfer* phase for the first time after a Digital Ping (see the *Qi Specification, Communications Protocol*). Subsequently, the Power Receiver may operate the output disconnect switch any time while the Power Transmitter applies a Power Signal.

**NOTE:** The Power Receiver may experience a voltage peak when operating the output disconnect switch (and changing between maximum and near-zero power dissipation).

Source: <a href="https://www.wirelesspowerconsortium.com/knowledge-base/specifications/download-the-qi-specifications/V-1.3-Power Delivery">https://www.wirelesspowerconsortium.com/knowledge-base/specifications/download-the-qi-specifications/V-1.3-Power Delivery</a>, Page 45

It is recommended that the Power Transmitter Product's power consumption in stand-by mode of operation meets the Energy Star EPS Requirements for "Energy consumption for No-Load" and the European Commission, Code of Conduct of Energy Efficiency of External Power Supplies for "No-load power consumption." It is also recommended that a Power Receiver is designed in a manner that when wireless power is not required, the Power Receiver will send an End Power Transfer Packet to put the Power Transmitter Product in stand-by mode.

Source: <a href="https://www.wirelesspowerconsortium.com/knowledge-base/specifications/download-the-qi-specifications/V-1.3-Power Delivery">https://www.wirelesspowerconsortium.com/knowledge-base/specifications/download-the-qi-specifications/V-1.3-Power Delivery</a>, Page 45

Further, to the extent this element is performed at least in part by Defendant's software source code, Plaintiff shall supplement these contentions pursuant to production of such source code by the Company.

[8.3] receiving from power the donor mobile device and converting received power into electric current using the wireless power transfer mechanism;

Company performs and induces others to perform the method of receiving power from the donor mobile device and converting received power into electric current using the wireless power transfer mechanism.

This element is infringed literally, or in the alternative, under the doctrine of equivalents.

For example, the Qi wireless power transfer system uses magnetic induction to transfer power from the power transmitter to the power receiver. Further, when charging begins, the magnetic field is picked up by the coil inside the Power Receiver and transformed by a power converter back into a direct electrical current that can be used to charge the battery.

# 3 How Qi wireless power transfer works

### 3.1 Basic concepts

The Qi wireless power transfer system uses magnetic induction to transfer power from a Power Transmitter Product (charger) to a Power Receiver Product (smartphone).

Source: <a href="https://www.wirelesspowerconsortium.com/knowledge-base/specifications/download-the-qi-specifications/V-1.3-introduction">https://www.wirelesspowerconsortium.com/knowledge-base/specifications/download-the-qi-specifications/V-1.3-introduction</a>, Page 8

When charging begins, the Power Transmitter runs an alternating electrical current through its coil(s), which generates an alternating magnetic field in accordance with Faraday's law. This magnetic field is in turn picked up by the coil inside the Power Receiver and transformed by a power converter back into a direct electrical current that can be used to charge the battery.

A critical feature of the magnetic field is that it can transfer through any non-metallic, non-ferrous materials, such as plastics, glass, water, wood, and air. In other words, wires and connectors are not needed between the Power Transmitter Product and Power Receiver Product.

PRx coil in smartphone

Magnetic field

PTx coil in charging pad

Figure 6. Qi wireless power transfer using magnetic induction

Source: <a href="https://www.wirelesspowerconsortium.com/knowledge-base/specifications/download-the-qi-specifications/V-1.3-introduction">https://www.wirelesspowerconsortium.com/knowledge-base/specifications/download-the-qi-specifications/V-1.3-introduction</a>, Page 9

Further, to the extent this element is performed at least in part by Defendant's software source code, Plaintiff shall supplement these contentions pursuant to production of such source code by the Company.

[8.4] wherein the wireless power transfer mechanism includes power adapter having coil, circuit elements to transfer power and a capacitor to store electric charge that increases battery life when the capacitor is discharged.

Company performs and induces others to perform the method wherein the wireless power transfer mechanism includes a power adapter having coil, circuit elements to transfer power and a capacitor to store electric charge that increases battery life when the capacitor is discharged.

This element is infringed literally, or in the alternative, under the doctrine of equivalents.

For example, the power receiver circuitry comprises a secondary coil, a series capacitor, and a rectifier ("circuit elements") such that the battery in the receiver gets charged. Further, the power receiver sends a signal to stop the power transfer to the power transmitter when wireless power is not required. Therefore, it would be apparent to a person having ordinary skill in the art that the capacitor is used for storing an electric charge which further increases the battery life of the power receiver.

Supply; in many cases a separate adapter such as a USB PD brick.

*Inverter*; a half-bridge or full-bridge for DC/AC conversion.


*Resonant Tank*; a coil and series capacitor boosting the power transfer capability.

*Resonant Tank;* a coil and series capacitor enhancing the power transfer efficiency.

Rectifier; either a diode bridge or an active (synchronous) bridge for AC/DC conversion.

Load; a battery with associated control circuitry.

Figure 2. Simplified model of a wireless power transfer system



Source: <a href="https://www.wirelesspowerconsortium.com/knowledge-base/specifications/download-the-qi-specifications/V-1.3-Power Delivery">https://www.wirelesspowerconsortium.com/knowledge-base/specifications/download-the-qi-specifications/V-1.3-Power Delivery</a>

**Power Signal:** An alternating magnetic field.

**Supply Power:** The power dissipated from the supply.

**Power Transmitter:** A subsystem that can generate a Power Signal.

**Power Transmitter Product:** 

A device containing one or more Power Transmitters.

**Transmitted Power:** The power from the Power Signal dissipated by any object that is not an

integral part of the Power Transmitter Product.

**Power Receiver:** A subsystem that can extract electric power from a Power Signal.

**Power Receiver Product:** 

A device containing a Power Receiver.

**Received Power:** The power from the Power Signal dissipated by any component that is

an integral part of the Power Receiver Product.

Source: <a href="https://www.wirelesspowerconsortium.com/knowledge-base/specifications/download-the-qi-specifications/V-1.3-Power Delivery">https://www.wirelesspowerconsortium.com/knowledge-base/specifications/download-the-qi-specifications/V-1.3-Power Delivery</a>

When charging begins, the Power Transmitter runs an alternating electrical current through its coil(s), which generates an alternating magnetic field in accordance with Faraday's law. This magnetic field is in turn picked up by the coil inside the Power Receiver and transformed by a power converter back into a direct electrical current that can be used to charge the battery.

A critical feature of the magnetic field is that it can transfer through any non-metallic, non-ferrous materials, such as plastics, glass, water, wood, and air. In other words, wires and connectors are not needed between the Power Transmitter Product and Power Receiver Product.

PRx coil in smartphone

Magnetic field

PTx coil in charging pad

Figure 6. Qi wireless power transfer using magnetic induction

Source: <a href="https://www.wirelesspowerconsortium.com/knowledge-base/specifications/download-the-qi-specifications/V-1.3-introduction">https://www.wirelesspowerconsortium.com/knowledge-base/specifications/download-the-qi-specifications/V-1.3-introduction</a>, Page 9

Figure 11 illustrates a simplified model of the system comprising a Power Transmitter on the left and a Power Receiver on the right. For clarity, the load circuit is drawn separately from the Power Receiver. The Power Transmitter consists of a power source  $(u_{\rm op}, f_{\rm op})$ , a capacitance  $C_{\rm p}$ , an inductance  $L_{\rm p}$ , and a resistance  $R_{\rm p}$ . The power source supplies a sinusoidal voltage  $u_{\rm op}$  at a frequency  $f_{\rm op}$ . The Power Receiver consists of a capacitance  $C_{\rm s}$ , an inductance  $L_{\rm s}$ , and a resistance  $R_{\rm s}$ .

A load having an impedance  $Z_L$  is connected to the output terminals of the Power Receiver. The symbols  $u_L$ ,  $i_L$ ,  $i_p$ , and  $k_{op}$  represent the load voltage, load current, Primary Coil current, and coupling factor.

PTx Power Transfer Interface

Figure 11. Simplified system model

Source: <a href="https://www.wirelesspowerconsortium.com/knowledge-base/specifications/download-the-qi-specifications/V-1.3-Power\_Delivery">https://www.wirelesspowerconsortium.com/knowledge-base/specifications/download-the-qi-specifications/V-1.3-Power\_Delivery</a>, Page 33

It is recommended that the Power Transmitter Product's power consumption in stand-by mode of operation meets the Energy Star EPS Requirements for "Energy consumption for No-Load" and the European Commission, Code of Conduct of Energy Efficiency of External Power Supplies for "No-

load power consumption." It is also recommended that a Power Receiver is designed in a manner that when wireless power is not required, the Power Receiver will send an End Power Transfer Packet to put the Power Transmitter Product in stand-by mode.

Source: <a href="https://www.wirelesspowerconsortium.com/knowledge-base/specifications/download-the-qi-specifications/V-1.3-Power\_Delivery">https://www.wirelesspowerconsortium.com/knowledge-base/specifications/download-the-qi-specifications/V-1.3-Power\_Delivery</a>, Page 45

Further, to the extent this element is performed at least in part by Defendant's software source code, Plaintiff shall supplement these contentions pursuant to production of such source code by the Company.

#### 2. List of References

- 1. <a href="https://www.samsung.com/us/mobile/galaxy-s20-5g/buy/galaxy-s20-fe-5g-128gb-unlocked-sm-g781uzbmxaa/">https://www.samsung.com/us/mobile/galaxy-s20-5g/buy/galaxy-s20-fe-5g-128gb-unlocked-sm-g781uzbmxaa/</a>, last accessed on 19 December, 2023.
- 2. <a href="https://www.samsung.com/us/support/troubleshooting/TSG01109653/">https://www.samsung.com/us/support/troubleshooting/TSG01109653/</a>, last accessed on 19 December, 2023.
- 3. <a href="https://www.samsung.com/us/support/answer/ANS00047798/">https://www.samsung.com/us/support/answer/ANS00047798/</a>, last accessed on 19 December, 2023.
- 4. <a href="https://www.wirelesspowerconsortium.com/knowledge-base/specifications/download-the-qi-specifications/">https://www.wirelesspowerconsortium.com/knowledge-base/specifications/download-the-qi-specifications/</a>, last accessed on 19 December, 2023.
- 5. https://www.youtube.com/watch?v=YcGLPV8Ov-o, last accessed on 19 December, 2023.